



外形尺寸 / Outer dimensions



钻臂摆角 / Swing angel of drill boom

水平钻孔范围 / Horizontal drilling range



 **浙江开山重工股份有限公司**
ZHEJIANG KAISHAN HEAVY INDUSTRY CO.,LTD.

地址：浙江省衢州市经济开发区凯旋南路10号
销售热线：400 870 0207
服务中心：400 826 6158
邮箱：kszhgy@kaishangroup.com
<http://www.zjkszg.com>
<http://www.kaishangroup.com>

Add: No.10 kaixuan Street(S),Quzhou,zhejiang.China
Sales phone: 400 870 0207
Service phone: 400 826 6158
E-mail:kszhgy@kaishangroup.com
<http://www.zjkszg.com>
<http://www.kaishangroup.com>

关注微信号
了解更多



开山集团



开山重工

 **开山重工**
KAISHAN HEAVY INDUSTRY

KT12型一体式露天潜孔钻车

KT12 Integrated Surface DTH Drilling Rig



品质开山 行业典范

KT12型一体式露天潜孔钻车

KT12 Integrated Surface DTH Drilling Rig

KT12型一体式露天潜孔钻车可钻凿垂直、倾斜和水平孔，主要用于大型露天矿山和石方工程钻凿爆破孔和预裂孔等。

KT12 integrated surface DTH drilling rig can drilling vertical, inclined and horizontal holes, mainly used for open-pit mine, stonework blast holes and pre-splitting holes.

以康明斯非道路柴油机为单一动力，通过两端输出的方式同时带动螺杆压缩系统和液压传动系统；

It is driven by the Cummins diesel engine and the two-terminal output can drive the screw compression system and hydraulic transmission system.

钻车配有自动接卸杆系统、钻杆浮动滑板模块、钻杆润滑模块，防卡钻系统、液压干式集尘系统、冷暖空调驾驶室等，并可选配钻孔角度和深度指示功能。

The drill rig is equipped with the automatic rod handling system, drilling rod floating slide module, drill pipe lubrication module, drill pipe sticking prevention system, hydraulic dry dust collection system, air conditioning cab, optional drilling angle and depth indication function, etc.



钻车具有整体性好、自动化程度高、凿岩效果好、环保节能、操作方便、机动灵活、行驶安全等特点。

The drill rig is characterized by excellent integrity, high automation, efficient drilling, environment-friendliness, energy conservation, simple operation, flexibility and travelling safety, etc.

技术参数 Technical Parameters

运输尺寸(长*宽*高) /Transport dimensions (L×W×H)	9900*2600*3350/3600 mm
重量 /Weight	17500 Kg
岩石硬度 /Rock hardness	f=6-20
钻孔直径 /Drilling diameter	115-152 mm
离地间隙 /Ground clearance	420 mm
履带调平角度 /Leveling angle of track	10°up, 10°down
行驶速度 /Travelling speed	0-3 Km/h
爬坡能力 /Climbing capacity	25°
牵引力 /Traction	120 KN
最大回转扭矩 /Rotary torque (Max)	3450 N·m (Max)
转速 /Rotation speed	0-120 rpm
钻臂举升 /Lifting angle of drill boom	向上47°, 向下20°/Up 47°, down 20°
钻臂摆角 /Swing angle of drill boom	向右50°, 向左15°/Right 50°, left 15°
滑架摆角 /Swing angle of carriage	向右96°, 向左30°/Right 96°, left 30°
滑架俯仰角 /Tilt angle of beam	114°
补偿行程 /Compensation stroke	1353 mm
推进行程 /Rotation Head stroke	4490 mm
最大推进力 /Maximum propelling force	40 KN
推进方式 /Method of propulsion	马达+滚子链/Motor + roller chain
经济钻孔深度 /Depth of economical drilling	28 m
容杆数量 /Number of rods	6+1
钻杆规格 /Specifications of drilling rod	Φ76/Φ89x4000 mm
冲击器 /DTH hammer	4吋、5吋/4"、5"
发动机 /Engine	康明斯QSL8.9-C360-30 Cummins QSL8.9-C360-30
气缸数 /Number of cylinders	6
输出功率 /Output power	264 KW / 2200 rpm
液压泵 /Hydraulic pump	5×齿轮泵/5× gear pump
螺杆机 /Screw compressor	两级压缩20m³/min /22bar /Two stage compression 20m³/min /22bar
行驶控制系统 /Traveling control system	液压先导/Hydraulic pilot
钻孔控制系统 /Drilling control system	液压先导/Hydraulic pilot
防卡 /Anti-Jamming	自动电液防卡 /Automatic electro-hydraulic anti-jamming
电压 /Voltage	24V 直流 /24V DC
安全驾驶室 /Safe cab	符合防落石&防翻滚标准 /Meet the requirements of ROPS & FOPS
室内噪声水平 /Indoor noise	低于85dB (A) /Below 85dB (A)
座椅 /Seat	可调 /Adjustable
空调 /Air-conditioning	标准冷暖 /Standard temperature
娱乐 /Entertainment	收音机+Mp3 /Radio +Mp3